



Foot Pedal



Model "E" Spider

Texas International MFG

Features & Applications

The Model "E" Pneumatic Spider is used to hold the load of the tubing string as it is lowered and raised from the well and can be operated by the remote foot valve. The load capacity for the Model "E" Spider is 175 Ton.

Size Range	2-3/8" - 7-5/8"
Operating Air Pressure	90 - 120 PSI

Body Size	Pipe Size	Net Weight LBS	Part Number
2-3/8" - 7-5/8"		950	T6600-100 (Body less slips)
3-1/2"	2-3/8"	19	T66651-1 (Inserts)
	2-7/8"	18	T66651-2 (Inserts)
	3-1/2"	105	T6600-3 (Slips & Inserts)
5-1/2"	4"	39	T66653-1 (Inserts)
	4-1/2"	33	T66653-2 (Inserts)
	5"	26	T66653-3 (Inserts)
	5-1/2"	93	T6600-2 (Slips & Inserts)
7"	6-5/8"	32	CE-0700-0610-0 (Inserts)
	7"	80	T66624-100 (Slips & Inserts)
7-5/8"	7-5/8"	85	T66624-102 (Slips & Inserts)

Spare parts available upon request
Non-marking dies available upon request

PRODUCT DESCRIPTION

Part No: T6600-100
Size Range: 2-3/8" - 7-5/8"
Weight less slips: 950 lbs.



We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.

Call now for a quote: 281-447- 3980