



DUETZ 6 Cylinder Diesel, Air Start - Tier 3 (Export)

**Skid Mounted Hydraulic Power Unit
Texas International Mfg**

Features & Applications



Deutz 6 cylinder, Diesel powered with Air Start, skid mounted hydraulic power unit.

- Hydraulic Output: 65 gpm
- Pump Options: Dual Stage
- Murphy Controller
- Hydraulic Cooler
- 100' of 1" & 1.25" Hydraulic Hoses

Specifications

Part No: TEXP914L06-AIR

Weight: 4,200 lbs.

Length: 98"

Width: 52"

Height: 63"

Item	Power (hp)	Speed (rpm)	Torque (ft/lbs)	Oil/filter change (hrs)	Fuel consumption
Deutz Air Cooled Diesel Engine*	113	2300	255	500**	6 gph***
	85	1500	295		

Tanks	Features	Volume (gal)	Working (gal)	Recommended Operating Temp (°F)
Hydraulic	Sight and temperature gauges	180	118	100 - 130
	Filtered breather			
	Top access hatch			
	Fully welded steel construction			
Diesel	Top access filler	57	55	N/A
	Fully welded steel construction			
	Sight and temperature gauges			
	Filtered breather			



We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.

Call now for a quote: 281-447- 3980