



500 Ton SX



X Series Type Elevators

**Texas International Mfg
Casing Tools**



250 Ton SLX

Features & Applications

SLX and SX should only be used with tubulars having square shoulder connections or lifting plugs. These elevator types consist of a stationary body and hinged door that allows entry and exit of tubulars. A safety pin fixed with a lanyard onto the elevator is included as an added feature to further prevent accidental openings.



150 Ton SLX

PRODUCT DESCRIPTION

SLX

- 2-3/8" - 5-3/4" 100 Ton
- 4-1/2" - 20" 150 Ton
- 4-1/2" - 30" 250 Ton
- 6-5/8" - 14" 350 Ton
- 42" 500 Ton

SX

- 7" - 18-5/8" 350 Ton
- 7" - 13-3/8" 500 Ton

SLX Part Numbers		
Size Range	Frame Part No.	Load Rating
2-3/8" - 2-7/8"	T33693-XXX	100 Tons
3-1/2" - 5-3/4"	T33854-XXX	100 Tons
4-1/2" - 9"	T31239-XXX	150 Tons
9-5/8" - 10-3/4"	T33950-XXX	150 Tons
11-3/4" - 13-5/8"	T33982-XXX	150 Tons
14" - 16"	T34087-XXX	150 Tons
16" - 20"	T33632-XXX	150 Tons
4-1/2" - 7-3/4"	T41239-XXX	250 Tons
8-5/8" - 10-3/4"	T43950-XXX	250 Tons
11-3/4" - 14"	T43982-XXX	250 Tons
16" - 20"	T43632-XXX	250 Tons
22" - 24-1/2"	T642540-XXX	250 Tons
26" - 30"	T642580-XXX	250 Tons
4-1/2" - 6"	T51239-XXX	350 Tons
6-5/8" - 9-7/8"	T53950-XXX	350 Tons
10-3/4" - 14"	T53982-XXX	350 Tons
42"	42ELEV	500 Tons

SX Part Numbers		
Size Range	Frame Part No.	Load Rating
7" - 13-3/8"	T29965-XXX	350 Tons
14" - 18-5/8"	T29966-XXX	350 Tons
7" - 13-3/8"	T29964-XXX	500 Tons



We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.

Call now for a quote: 281-447- 3980